

Nonwoven Substrates



Product Data Sheet

Attributes & Properties

Name: 95SP INTREPID® Filtration Media

Color: Yellow / White

Basis Weight: 5.20 ounces per square yard

(176 grams / square meter)

Efficiency: 92.0 %

TSI Model 8130 automated filter tester with 0.1 µm count median diameter NaCl particles

at 85 liters per minute.

Air Permeability: 50 cubic feet of air/minute per square foot of media

(0.25 cubic meter of air / second per square meter of media)

Textest FX 3300 Labotester III

Thickness: 0.150 inches

(3.81 millimeters)

Testing load of 0.025 psi (172.4 Pascals)

Inside Core: 3 inches

Diameter (76.2 millimeters)

Roll Length: 180 linear yards

(165 linear meters)

1400 Holcomb Bridge Road Roswell, Georgia 30076-2199 Phone: 770-587-8000 www.kcprofessional.com

[⋄] Unless otherwise noted, the material described in this document is available for commercial sale and sold with a limited warranty. Kimberly-Clark Corporation and/or Kimberly-Clark Worldwide retains all intellectual property rights to this material, including trademarks and trade names. If the material described is defined as developmental, the material properties are estimates only and are not warranted by Kimberly-Clark Corporation.